

AMENDMENTS TO THE CLAIMS

The claims in this listing will replace all prior versions, and listings, of claims in the application.

LISTING OF CLAIMS:

1. (Currently Amended) A thermal overload relay comprising:

an ~~actuating mechanism for generating~~ actuator that generates power when an abnormal state ~~is occurred~~ occurs in a circuit between a power source and an electrical load;

a ~~switching mechanism for switching~~ switch that switches contacts ~~to an on state or off state~~ according to the power transferred from the ~~actuating mechanism actuator~~; and

a case ~~for receiving~~ that receives the ~~actuating mechanism actuator~~ and the switching mechanism;

wherein the ~~actuating mechanism including actuator~~ further comprises:

a plurality of main bimetals arranged such that a longitudinally extending direction of each main bimetals is generally ~~in parallel to the~~ a bottom surface of the case ~~for being bended~~ and configured to bend when the abnormal state is ~~occurred~~ occurs;

a plurality of heating member members, each of the heating member members is wound around the a corresponding main bimetal ~~for transferring to transfer~~ heat ~~occurred~~ , occurring due to the abnormal state, to the main bimetal;

a shifter positioned to ~~be contacted one~~ contact ends of the main bimetals and arranged in parallel to the bottom surface of the case ~~for being such~~ that the shifter is horizontally movable by the bending force of the main bimetals; and

a lever connected to the shifter ~~for transferring~~ that transfers the movement force from the shifter to the ~~switching mechanism~~ switch,

wherein a temperature compensation bimetal contacts an end of the lever.

2. (Currently Amended) The thermal overload relay according to claim 1, wherein the shifter ~~comprising~~ comprises an upper shifter and lower shifter ~~so that they are~~ positioned on a vertical plane, wherein each shifter is arranged in substantially generally perpendicular to the ~~one end of the main bimetal~~ ends of the bimetals, and in parallel to the bottom surface of the case.

3. (Currently Amended) The thermal overload relay according to claim 1, wherein the shifter ~~comprising~~ comprises an upper shifter and a lower shifter ~~so that they are~~ positioned on a vertical plane, each shifter is arranged in substantially generally perpendicular to the ~~one end of the main bimetal~~ ends of the main bimetals, and in parallel to the bottom surface of the case, and the shifter further ~~comprising a pair of shaft for connecting~~ comprises shafts that connect the lever to the upper shifter and the lower shifter respectively, so as to

P24396.A03

transfer the displacement amount generated by the bending force of the main bimetals to the ~~switching mechanism~~ switch.